

# Lufft WS500-UMB – Temperature, Air Pressure, Relative Humidity, Wind, Electronic Compass

From the WS product family of professional intelligent measurement transducers with digital interface for environmental applications.

Integrated design with ventilated radiation protection for measuring:

- Air temperature
- Relative humidity
- Air pressure
- Wind direction
- Wind speed

Relative humidity is measured by means of a capacitive sensor element; a precision NTC measuring element is used to measure air temperature.

Ultrasonic sensor technology is used to take wind measurements.

Measurement output can be accessed by the following protocols:  
UMB-Binary, UMB-ASCII, SDI-12, MODBUS

Lufft WS500-UMB Compact Weather Station			Order No.
<b>WS500-UMB</b>			<b>8373.U01</b>
<b>Technical Data</b>	Dimensions	Ø approx. 150 mm, height approx 287 mm	
	Weight	approx. 1.2 kg	
<b>Temperature</b>	Principle	NTC	
	Measuring range	-50 ... 60 °C	
	Accuracy	±0.2 °C (-20 °C ... +50 °C), otherwise ±0.5 °C (> -30 °C)	
<b>Relative humidity</b>	Principle	Capacitive	
	Measuring range	0 ... 100 % RH	
	Accuracy	±2 % RH	
<b>Air pressure</b>	Principle	MEMS Capacitive	
	Measuring range	300 ... 1200 hPa	
	Accuracy	±1.5 hPa	
<b>Wind direction</b>	Principle	Ultrasonic	
	Measuring range	0 ... 359.9 °	
	Accuracy	±3 °	
<b>Wind speed</b>	Principle	Ultrasonic	
	Measuring range	0 ... 60 m/s	
	Accuracy	±0.3 m/s or ±3 % (0 ... 35 m/s)	
<b>General Information</b>	Heating	20 VA at 24 VDC	
	Protection type housing	IP65	
	Interface	RS485, 2-wire, half-duplex	
	Op. power consumption	24 VDC +/-10 %	
	Operating humidity range	0 ... 100 %	
<b>Accessories</b>	Op. temperature range	-50 ... 60 °C	
	Surge protection		<b>8379.USP</b>
	Power supply 24V/4A		<b>8366.USV1</b>
	UMB Interface converter ISOCON-UMB		<b>8160.UISO</b>
	Traverse for R2S-UMB + WS500-UMB		<b>8367.TRAV</b>
	Digital-analog-converter DACON8-UMB		<b>8160.UDAC</b>
	Temperature Sensor WT1		<b>8160.WT1</b>
	Surface Temperature Sensor WST1		<b>8160.WST1</b>
	Rain Sensor WTB100		<b>8353.10</b>

Ultrasonic wind sensor  
Aspirated temperature/humidity measurement  
Open communication protocol:  
- UMB-ASCII  
- UMB-Binary  
- SDI-12  
- MODBUS  
- Analogue outputs in combination with 8160.UDAC

