

RH300: PSICRÔMETRO DO HIGROTERMÔMETRO

Descrição:

Medições de umidade, bulbo úmido, ponto de condensação, temperatura do ar, além de temperatura de sonda externa

Recursos:

Exibição simultânea de %UR, temperatura e ponto de condensação ou termômetro molhado ou temperatura de sonda

Medições de termômetro molhado sem suspensão

Calcula o diferencial T1-T2 (Temperatura do ar – Temperatura da sonda externa) usando sonda opcional

O design exclusivo da tampa com sensor gira para a posição fechada para proteção durante o armazenamento

Unidades de temperatura °F/°C intercambiáveis com resolução de 0,1°



RH300-CAL Optional calibration salt bottles



RH305 Digital Psychrometer Kit includes RH300, 33% and 75% calibration bottles, temperature probe, and carrying case.



Unique sensor cap design
Twist to open or close sensor for storage.

Specifications:	Range	Max Resolution	Basic Accuracy
Humidity	10 to 90%RH	0.1%RH	±3%RH
Temperature (internal)	-4 to 122°F (-20 to 50°C)	0.1°	±1°F or ±0.6°C
Temperature (external)	-4 to 158°F (-20 to 70°C)	0.1°	±1°F or ±0.6°C
Dew Point	-90.4 to 122°F (-68.0 to 49.9°C)		
Wet Bulb	-6.9 to 122°F (-21.6 to 49.9°C)		
Dimensions	7 x 1.9 x 1" (178.5 x 48.4 x 24.7mm)		
Weight	3.3oz (95g)		